



- 








| | |
|--------------|----------------------------------|
| Product name | START WATERPROOF 1200 HOUSING 1X |
| Technology | LED |
| Cap/Base | 2G13 |
| Housing | PC Polycarbonate |
| Mount | Wall surface mounted |

Start Waterproof Housing

START WATERPROOF 1200 HOUSING 1X

0047193

| | |
|----------------------------------|----------------------|
| General application | Logistics & Industry |
| Operating temperature range (°C) | -20°C...+40°C |
| ETIM Class | EC002892 |
| E-number FI | 4357155 |
| Warranty | 5 years |

Optical data

| | |
|---------------------------------|----------------|
| Fixture luminous flux (lm) | 1 |
| Luminaire efficacy (lm/W) | 1 |
| Light colour | N/A |
| Colour Variation Initial (SDCM) | N/A |
| Distribution type | Symmetric |
| Photobiological Risk Group | Not applicable |

Electrical data

| | |
|--|-----------------------------|
| Light source included | Fixture without Lightsource |
| Total power consumption (W) | 0.1 |
| Primary Supply/Product voltage - min (V) | 220.0 |
| Primary Supply/Product voltage - max (V) | 240.0 |
| THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x % | 10 |
| Electrical protection | Class II |
| Control gear type | Not required |
| Dimmable | No |
| Dimming method | N/A |
| Glow Wire Test (°C) | 650 |
| Nominal Frequency (Hz) | 50/60Hz |
| Max. products per 10A C Breaker | 1 |
| Max. products per 16A C Breaker | 1 |
| Max. products per 16A B Breaker | 1 |
| Connectable conductor cross section - Max (mm²) | 1.5 |

Lifetime data

| | |
|------------------|-------|
| Lifespan L70 B50 | 25000 |
|------------------|-------|

Physical data

| | |
|-----------------------------|------------------|
| Housing colour | Grey |
| IP rating | IP65 |
| IK rating | IK08 |
| Diffuser finish | Transparent |
| Diffuser material | PC Polycarbonate |
| Nominal Product Length (mm) | 1280 |
| Nominal Product Width (mm) | 65 |
| Nominal Product Height (mm) | 60 |
| Weight (kg) | 0.7 |

Packaging

| | |
|--------------------|---------------|
| Product EAN number | 5410288471938 |
|--------------------|---------------|



Start Waterproof Housing

START WATERPROOF 1200 HOUSING 1X

0047193

| | |
|---------------------------------------|----------------|
| Packaging single length / height (cm) | 133.5 |
| Packaging single width (cm) | 6.4 |
| Packaging single depth (cm) | 4.5 |
| DUN14 (outer) | 15410288471935 |
| Units per outer package | 12 |
| Packaging outer length / height (cm) | 135.0 |
| Packaging outer width (cm) | 15.9 |
| Packaging outer depth (cm) | 28.4 |

| | |
|----------------------------------|--------|
| Safety data | |
| Optimal operating condition (°C) | -20-40 |