



ASUS ZenBeam™ E2 LED Projector

Auto Portrait Mode for Unmatched Versatility



Key Features



300
LED Lumens

Up to 300 LED lumens light output delivers bright visuals



Supporting 480P resolution 125% sRGB color saturation for clear image quality



1.15 meter provides a 40" display, for projected images measuring from 40 inch (1m) to 100 inch (2.8m)

LED
Light Source
30,000 hrs Lifetime

LED light source for greater color and brightness performance



Auto Keystone Correction


Auto vertical keystone correction ensures perfect projection



Provide 5W speaker with SonicMaster technology for rich sound quality

Wireless Projection Ready

Eliminate hassle, let you effortlessly project with your mobile devices anywhere




Auto Portrait mode

Auto Portrait mode offer automatically transitions while wireless projection



Built-in rechargeable battery power, up to 4 hour battery life

| | | | | | |
|---|--|-----------------------------------|--|---|--|
| Display | Display Technology : 0.2" DLP® Light Source/ Life (Max) : R/G/B LED, 30,000 hours True Resolution (Native) : 480P 854 x 480 Maximum Input Resolution : 1920 x 1080 Light Output (Max) : 300 LED lumens Contrast Ratio : 400:1 (Typical) Color Saturation : 125% sRGB Display Colors: 16.7 million Colors | | | | |
| Projection Lens | Throw Ratio (@16:9) : 1.3:1 Projection Distance / Size : 0.76 ~ 2.54 meters / 30 ~ 100 inches Projection Offset : 100 % Focus: Manual Zoom Ratio : Fixed | | | | |
| Video Feature | Picture Modes : 3 modes (Presentation / Standard / Theater) Keystone adjustment : Vertical keystone correction Auto Keystone : Yes, Vertical(± 40°) Projector Placement : Front Table, Rear Table, Front Ceiling, Rear Ceiling | | | | |
| Audio Features | 5W Speaker, ASUS SonicMaster technology | | | | |
| I/O Ports | <table border="0"> <tr> <td>Signal Input : HDMI x 1</td> <td>USB : USB-A – USB Wi-Fi dongle/ power output</td> </tr> <tr> <td>Earphone out : Yes, 3.5mm Mini-jack</td> <td></td> </tr> </table> <div style="text-align: center; margin-top: 10px;">  <p>The diagram shows three ports in a row: an HDMI port on the left, an Earphone Out port in the center, and a USB-A port on the right. Each port is labeled with its respective name above it.</p> </div> | Signal Input : HDMI x 1 | USB : USB-A – USB Wi-Fi dongle/ power output | Earphone out : Yes, 3.5mm Mini-jack | |
| Signal Input : HDMI x 1 | USB : USB-A – USB Wi-Fi dongle/ power output | | | | |
| Earphone out : Yes, 3.5mm Mini-jack | | | | | |
| Wireless Projection | Yes, Support Android, iOS and Windows 10 devices | | | | |
| Wi-Fi | Yes, USB Wi-Fi dongle | | | | |
| Power Consumption | Power On (Max): <36.5W Power Standby Mode : <0.5W* | | | | |
| Internal Battery / Battery Life | 6000mAh / Up to 4 hours* | | | | |
| Acoustic Noise (max) | 30dBA (Standard mode), 28dBA (Theater mode) | | | | |
| Mechanical Design | Tripod Socket : Yes Adjustable stand: Yes | | | | |
| Dimensions | Phys. Dimension (WxHxD) : 110 x 39.5 x 107mm Box Dimension (WxHxD) : 140 x 135 x 172mm | | | | |
| Weight | Net Weight (Esti.) : 410 g Gross Weight (Esti.) : 500 g | | | | |
| Operation Temperature | 0 ~ 40 °C | | | | |
| Operation Humidity | 20 ~ 90 % | | | | |
| Accessories | Carrying bag, Power adapter, AC plug, HDMI Cable, WiFi dongle(Model name:EZC-5201BS) , Quick start guide, Warranty card | | | | |
| Compliance Standards | FCC / CE / CB / CCC / RCM / VCCI / CU / IEC62471 / CEC | | | | |

*Based in Low mode usage

*The battery has a lifespan and ages every time when it is charged and discharged. It will gradually lose its charging capability as it ages.

*All specifications are subject to change without notice.