A decabate	Factor.		M/0040	tem Specificati		M/O/100	MV(0200
Module	Features		MVC940	MVC840	MVC640	MVC400	MVC320
			10 10		i G		-0
				FF			
	Target Roo	m Size	Extra large rooms	Large rooms	Medium rooms	Small rooms	Focus rooms
Components	Mini-PC			The state of the s	Yealink MCore		
	Touch Console & Sharing Device		Yealink MTouch II				
	USB Camera		Camera Hub 2x Yealink UVC84 4k 12X optical PTZ camera	Yealink UVC84 4K 12X optical PTZ camera	Yealink UVC84 4K 12X optical PTZ camera	Yealink UVC40 all-in-one USB video bar	Yealink UVC30 Room 4K camera
	Audio		Flexible options	2x VCM34 array mics+Yealink soundbar 3x VCM34 array mics + 2x Yealink soundbar	Yealink MSpeech tabletop speakerphone		Yealink MSpeech tabletop speakerphone
	Wireless Pr	esentation	2x WPP20	Optional	Optional	Optional	Optional
MCore MTouch II	CPU		8th-gen Intel QUAD-CORE i5-8265U				
	Memory		8GB (2*4GB)				
	Storage		128GB SSD				
	Video Output		2x HDMI, CEC supported				
	USB Wi-Fi		4x USB3.0				
	Wi-Fi		√				
	Yealink VCH Port		4				
	Gable Management		J.				
	Screen Size		8 inches IPS screen				
	Screen Resolution		1280 x 800				
	Bracket		Adjustable 28° – 50°				
	Human Motion Sensor		√				
	3.5mm Audio Port		1				
	USB-A Port		1x USB-A Port, connect to USB audio device if necessary				
	Content Sharing Resolution / Frame Rate						
	Video Input interface for Content Sharing		HDMI & USB-C				
	Built-in Wi-Fi AP for Content Sharing Wireless Content Sharing		1				
	UVC Protocol		Work with Yealink WPP20 wireless presentation pod UVC 1.0				
Camera Features	Zoom		12X optical	12X optical	12X optical	8X digital	3X digital
	Resolution / Frame Rate		4K / 30FPS	4K / 30FPS	4K / 30FPS	4K / 30FPS	4K/30FPS
	Field of View(diagonal)		80°	80°	80°	133°	120°
	Pan/Tilt range		200°/130°	200°/130°	200°/130°	E-PTZ	E-PTZ
	Auto Framing		1	√	1	J.	1
	Speaker Tracking		×	×	×	√	×
	Audio Ports		1x Yealink Microphone port + 1x Line-out ports	1x Yealink Microphone port + 1x Line-out ports	1x Yealink Microphone port + 1x Line-out ports	1x Yealink Microphone port + 1x Line-in port	NA
	Power Adapter		AC 100~240V Input and DC 48V/0.7A Output	In the second of the second se	AC 100~240V Input and DC 48V/0.7A Output	AC 100~240V Input and DC 48V/0.7A Output	NA
Carnera-hub	Gamera Layout		Support camera layout including full screen, surrond, division		NA	NA	NA
	Maximum number of cameras		Up to 9 UVC84 camera	hone port +			
	Audio Ports		1x Yealink Microphone port + 1x RCA-in & 1x RCA-out ports				
Audio Features	Speaker	Frequent Response	100 Hz - 20K Hz	100 Hz - 20K Hz	100 Hz - 20K Hz	100 Hz - 20K Hz	115 Hz -16 KHz
		RMS	10W	10W	10W	3W	4W
		THD	1.00%	1.00%	1.00%	1.00%	1.00%
		Maximum Speakers	Up to 4 (optional)	Up to 4	NA	NA	NA
	Microphone		Mutiple VGM34 array mics (optional)	2~3 VCM34 array mics	1x MSpeech Speakerphone	Built-in microphone	1x MSpeech Speakerphor
			Built-in 3-mic array	Built-in 3-mic array	Built-in 3-mic array	8 MEMS mic array	Built-in 3-mic array
			20ft(6-meter) voice	20ft(6-meter) voice pickup range	20ft (6-meter) voice pickup range	Beamforming microphone technology	20ft (6-meter) voice
			pickup range Cascade connection	Cascade connection			pickup range
			up to 6 units	up to 6 units	NA	NA	NA
Preload	Operating System		Windows 10 IoT Enterprise OS & License				
	Microsoft Teams Rooms App		J				
	Yealink RoomConnect Device Management Agent		√				
	Windows Update		J				
Device Management	Yealink Device Management Platform/Cloud Service		√ √				
	Microsoft SCCM		· ·				
		VOIVI	J				



Microsoft Teams Rooms System for Large Room

Yealink MVC series are native and easy-to-use video conferencing solutions specially designed for Microsoft Teams rooms. The MVC series provides a full-scene video conference solution to cover all of the meeting rooms from small to large. According to the unique characteristics of the video conferencing room, a high-performance mini-PC is specially released. In the design of mini-PC, it takes into account both aesthetics and practicability, that fully integrating the cable management with itself to provide a flexible and reliable deployment solution for any meeting room. The MVC series features the native Microsoft Teams-tailored user interface that is easy to be operated with close-to-zero learning curve, and you just walk into the meeting room and start your scheduled Teams or Skype for Business meeting with one-touch join. Yealink MVC840 includes two or three VCM34 array microphones (up to 6 units can be connected) and a 4K UVC84 USB PTZ camera with 12x optical zoom to meet the requirements of large meeting room.



One Cable

Technology



3-Microphone





Control Plug-in







Wireless Device
Content Sharing Management



Key Features and Benefits

Native Microsoft Teams-tailored user interface, smooth conference experience

Yealink Camera Auto Framing

Native Microsoft Teams-tailored user interface offers a one-touch meeting join. Designed with the idea of multi-function all-in-one, the MTouch II touch panel allows you easily perform call control, camera control, content sharing and other functions. At the same time, MTouch II has a built-in Human Motion Sensor that the conference system can be automatically waken up and you can immediately start the conference.

Auto-framing & smart noise proof technology

Yealink UVC84 camera allows for the auto-framing of all participants present at a meeting, freeing your hands and focusing on the meeting itself. Meanwhile, with the Yealink camera control plug-in and camera presets supported, the mechanical pan, tilt and zoom can be easily done quietly in one step. Empowered with 12x optical zoom, UVC84 supports 4K video calls that conducts business to capture everyone in the meeting room clearly. As for the audio, the VCM34 array microphone supports 20ft/360° voice pickup range and works with Yealink Soundbar together to guarantee you a high-quality audio solution. Also, Yealink Noise Proof technology effectively eliminates background distractions and noises that you can enjoy a crystal-clear voice even in a noisy environment.

Content sharing in real time

The unique wireless content sharing solution provides participants with maximum flexibility, that a one-click content sharing can be simply realized by plugging into the WPP20 only. With a high resolution of 1080P/30 frames, it provides users with a better content sharing experience. Besides, the wired content sharing is also available by connecting to the USB-C port or HDMI port.

Simple to deploy, easy to use

With the VCH port, MCore is specially designed for the video meeting rooms that the deployment can be easily extended. At the same time, its all-in-one design with the feature of cable management ensure the stability of the wire connection, and the most appropriate deployment can be achieved according to the layout of the meeting room. One CAT5e is totally enough to connect the TV area and the conference table area and to complete the data transmission and power supply, no additional power supply or extension cable is needed, which not only simplifying the deployment but also effectively reducing deployment costs.

Manage your devices remotely

This solution supports Yealink Device Management Platform/Cloud Service, you can flawlessly manage, monitor, configure, update and diagnose all Yealink audio and video devices peripherals on this platform remotely.





Package Content

- MCore Mini-PC
- MTouch II touch panel
- UVC84 USB PTZ camera
- Two or three VCM34 array microphones (optional)
- One or two Yealink soundbars (optional)
- WPP20 wireless presentation pod (optional)

Preload

- Windows 10 IoT Enterprise X64
- Windows 10 IoT Enterprise License
- Microsoft Teams Rooms App, support Skype for Business on-premise/online and Teams meetings
- Yeallink RoomConnect

MCore Mini-PC

- 8th-gen Intel® QUAD-CORE i5
- Memory: 8GB (2 x 4GB)
- Storage: 128GB SSD
- 2 x HDMI video output with CEC supported
- · Bluetooth and Wi-Fi
- 1x Yealink VCH port (RJ45), connect to MTouch II
- 4 x USB3.0 Type-A
- 1 x 10/100/1000M Ethernet port
- 1 x Power port
- 1 x Security lock slot
- Integrated cable management

MTouch II touch panel

- 8-inch IPS screen
- 1280 x 800 resolution
- 10-point capacitive touch screen
- 3.5mm headset jack
- · Human Motion Sensor
- Angle adjustable bracket (28° ~ 50°)
- 1080P/30FPS FHD for sharing
- · Support wired and wireless content sharing
- Built-in Wi-Fi AP for Yealink wireless presentation device
- HDMI/USB-C HD video input

UVC84 USB PTZ Camera

- 4K camera
- 12x optical zoom
- Field of view (diagonal): 80°
- Auto Framing
- · Camera presets
- Pan range: 200°
- Tilt range: 130°
- 1 x Line-out (3.5mm)
- 1 x Yealink Microphone port (RJ-45)
- 1 x USB 2.0 Type-B
- 1 x Power port
- 1 x Security lock slot
- 1 x Reset slot

VCM34 Array Microphone

- Built-in 3-microphone array
- 360° 20ft (6-meter) voice pickup range
- · Cascade connection up to 6 units
- Mute button with bicolor LED

Yealink Soundbar

• Frequent response: 100Hz - 20KHz

• S/N: ≥70dB

1 x Line-in (3.5mm)

Package Features (2 x VCM34)

• N.W/CTN: 10.4Kg

• G.W/CTN: 11.6Kg

• Carton Meas: 595mm x 535mm x 320mm

Package Features(3x VCM34)

N.W/CTN: 12.9Kg

• G.W/CTN: 14.1Kg

• Carton Meas: 595mm x 535mm x 320mm

Package Features(without audio)


N.W/CTN: 6.6Kg

• G.W/CTN: 7.3Kg

Carton Meas: 595mm x 393mm x 258mm


Scene Graph in a Conference Room








Connection



- When starting up the system for the first time, you need to connect a mouse to complete the initial configuration. We recommend using the wireless mouse and keyboard kit.
- For more information about the installation and deleployment of accessories (for example, the installation of MCore package or the UVC84 camera), refer to the Quick Start Guide of corresponding accessory.



Optional audio device connection





About Yealink

Yealink (Stock Code: 300628) is a global brand that specializes in video conferencing, voice communications and collaboration solutions with best-in-class quality, innovative technology and user-friendly experience. As one of the best providers in more than 140 countries and regions, Yealink ranks No.1 in the global market share of SIP phone shipments (Global IP Desktop Phone Growth Excellence Leadership Award Report, Frost & Sullivan, 2019).

Copyright

Copyright © 2021 YEALINK(XIAMEN) NETWORK TECHNOLOGY CO., LTD.

All rights reserved. No parts of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, photocopying, recording, or otherwise, for any purpose, without the express written permission of Yealink(Xiamen) Network Technology CO., LTD.

Technical Support

Visit Yealink WIKI (http://support.yealink.com/) for firmware downloads, product documents, FAQ, and more. For better service, we sincerely recommend you to use Yealink Ticketing system (https://ticket.yealink.com) to submit all your technical issues.



YEALINK(XIAMEN) NETWORK TECHNOLOGY CO.,LTD. Web: www.yealink.com Addr: No.1 Ling-Xia North Road, High Tech Park,

Huli District, Xiamen, Fujian, P.R. China Copyright©2021 Yealink Inc. All right reserved.